



ATOM Full HD ~ D1

AT 0616V-H9D

16/9 Channel Hybrid Video Recorder

Superior Engineering Design & Sensational Image Quality

AT 0616V-H9D

16/9 Channel Hybrid Video Recorder

Features :

- H.264 Main Profile Hardware compression with iH3
- Support Full HD/HD/D1/CIF Real Time Recording
- Support Intelligent features iCloud Monitoring
- HDMI 1080P / VGA 1080 / TV Simultaneously Viewing Output
- 3G / Wifi / uPnP Connectivity
- Multi Channel Simultaneously Playback
- Record & Network Stream(CIF/QCIF) Dual Stream Selectable
- Central Monitoring Station Support up to 128CH with 99 Sites
- Multiviewing Single Windows Screen up to 64 CH on Display Monitor
- Support 2 HDD up to 6TB(3TB*2)
- Free DDNS Server with Very Easy & User Friendly
- DDNS Server Compatible with Anorid/I-Phone Handsets
- Anorid Mobile Handset with Remote Playback, Local Record & Snap Shot Capture
- Supports Anorid, I-Phone, Windows 6.1, Symbian S60 3rd & Blackberry
- Support All Popular Web browser (IE, Firefox, Anorid, Safari)
- All Channel Network Playback ON Internet Explorer(IE)
- All Configuration Setting can be done through Locally & Remotely by IE or CMS.
- Digital Zooming on Internet Explorer, Live & Playback
- Email Alerts when motion is detected, Video Loss
- Support Email, FTP, Buzzer, when Alarm Motion, Video Loss, Video Blind & Etc
- Back UP Threw Network, USB portable HDD, USB DVD-RW.
- Back UP Directly With AVI or H.264, External Back up to 2TB
- User Friendly GUI & OSD for easy & fast operation.
- 4CH Alarm Input (Optional)
- Various brand PTZ Protocol with facility preset, cruise and PTZ Function.
- Front Panel Keypad, Mouse & Remote control
- Lowest Power Consumption.
- Support Multi Language.



Specifications :

Model No	AT 0616V-H9D
System	
Hardware Compression	H.264 Main Profile Compression
Operation System	Embedded Linux
System Operation	All CH Record & Playback, Multi User Network Operat. Simultaneously & USB Backup
Signal System	PAL / NTSC Selectable
Record/Playback/Streaming	
Record Resolution	FullHD(1080)/HD(720)/D1/CIF
Record Quality	Best/Better/Good/Normal/Worst
Record Stream Bit Rate	VBR / CBR
Record Type	Sechedule, Manual, Alarm, Motion Based
I Frame Interval	2 ~ 12 Selectable
Sub Stream	CIF/QCIF
Sub Stream Frame Rate	1 ~ 12/25 fps
Sub Stream Bit Rate	VBR / CBR(up to 512KBPS)
Digital Parameter	
DVR MODE	
Record Selection	2CH D1 + 14CIF or 16CH @ CIF
Record Frame Rate	1 ~ 25/30fps Selectable for All Resolution
Playback Channel	8 CH or 16CH
Playback Frame Rate	1 ~ 25/30fps @ Playback Channel Selection
Hybrid MODE	
Channel Selection	2CH Analog + 2CH IP
Record Selection	Analog 2CH D1 + IP 1CH @ 1080P + 1CH @ 720P
Record Frame Rate	1 ~ 25/30fps Selectable for All Resolution
Playback Channel	2CH
Playback Frame Rate	1 ~ 25/30fps @ Playback Channel Selection
NVR MODE	
Record Selection	Full HD/HD/WD1/D1

Specifications :

Channel Selection	9CH @ D1, 8CH @ WD1, 4CH @ HD, 2CH @ Full HD, 4CH @ D1*2,HD*1, Full HD*1,
Record Frame Rate	1 ~ 25/30fps Selectable for All Resolution
Playback Channel	9CH/8CH/4CH/2CH
Playback Frame Rate	1 ~ 25/30fps @ Playback Channel Selection
Video/Audio/Interface	
Video Input	16CH Input, BNC Connector
Video Impedance	1.0Vp-p,75Ω
IP Camera Input	9CH
Video Output	HDMI(1080P) X 1, VGA(1024) X 1, Composite Video(1.0Vp-p,75Ω) X 1
Audio Input	6CH, RCA Connector
Audio Impedance	200-2800mV,30KΩ
Audio Output	1 CH RCA, 200-3000mV,5KΩ
Network	RJ45 - 10/100MBPS Auto Detection
PTZ Control	Rs485
USB	3 Port (USB 2.0, USB 1.1)
Harddisk Interface	2 HDD (SATA Port)
Harddisk Capacity	Max. up to 3TB Each Port
DVD-RW	Optional BY SATA Interface
Special Function	
3G Dongle Support	YES
WIFI Connectivity	YES, Via WIFI Dongle Devices(Dongle Optional), No 3G Connected
uPnP	YES
Email Alert	Video Loss, Video Blind, Motion Detection
FTP Upload	Video Blind, Motion Detection
Digital Zooming	YES
Network Protocol	Static IP/DHCP/PPPoE/NTP/EMAIL/IP Filter/FTP/Wireless Config/ RTSP
Back Mode	Via USB HDD/ PEN DRIVE, USB DVD-RW or Internal DVD-RW
Motion Detection	16 × 12 grids per channel, 6 adjustable parameters

Specifications :

Software Support	
CMS	up to 128Channel
CMS Remote Site	up to 99 Different Site DVR in Single CMS
CMS Viewing on Main Screen	4 ~ 64 Channel on one Screen
Mobile Handset	I-Phone, IPAD, Anorid, Blackberry, Symbian S60, Windows
Web Browser	IE, Firefox, Safari, Chrome
DDNS Server	YES with DYNDNS/NO-IP or ARSP(Own Server)
MAC Safari	YES
General	
Language	English, Spanish, French, German, Chinese & Many More
Local Operation	By Front Panel Keys, Mouse, Remote Controller
Power Supply	DC 12V/4 Amp Power Adaptor
Power Consumption	<20W without HDD
Operating Temperature	0°C ~ +55°C
Operating Humidity	10% ~ 90% RH
Dimensions(W×D×H)	DVR: 353*325*61 mm, Box 410*415*135mm,
Weight (g)	3.5Kg Apporx., Without Box
Enclosure	Metal with ABS Plastic Front Panel

* Product specifications and appearance may be changed without prior notice due to improvements.



Scan with your
Smart phone for
more information
www.avtrontech.com

AVTRON

www.avtrontech.com | info@avtrontech.com